

# MDG

# NEW



## The Non-Stop LOW FOG Generator

Using refrigerated liquid CO<sub>2</sub> as a coolant and CO<sub>2</sub> Gas as a propellant

- Produces the DENSEST Low Fog •
- Lowest fluid consumption •
- Noiseless •
- Adjustment of output •
- Three safety systems •

# ICE FOG TOURING

## LOW FOG GENERATOR

### TECHNICAL DATA

<b>CO<sub>2</sub> type:</b>	Refrigerated liquid CO <sub>2</sub> (dewar)
<b>CO<sub>2</sub> consumption:</b>	3 l (6,8 lb) per minute at 13,75 bar (200 psi)
<b>Fluid type:</b>	MDG Low Fog Fluid <b>only</b> – M.S.D.S. available on request
<b>Fluid consumption:</b>	0,07 l (2,2 oz) per minute at full volume
<b>Reservoir capacity:</b>	2,5 l (0,66 US gallon)
<b>Fog color:</b>	Pure white
<b>Particle size:</b>	1 - 3 microns
<b>Warm-up time:</b>	10 min.
<b>Operating voltage:</b>	230 VAC, 50/60Hz
<b>Power consumption:</b>	2850 Watts
<b>Dimensions:</b>	1,55 m (61")L * 66 cm (26")W * 76 cm (30")H
<b>Weight:</b>	80 kg (175 lb)
<b>Approval:</b>	CE approved, CSA and UL pending

Les Générateurs de Brouillard MDG Ltée / MDG Fog Generators Ltd  
5639 Christophe-Colomb, Montreal, QC, Canada H2S 2E8  
Tel: 514 272-6040 / 800 663-3020 • Fax: 514 722 3229  
www.MDGFOG.com • e-mail: info@MDGFOG.com

