

NEW

MDG

ICE FOG LFG

LOW FOG GENERATOR

The Non-Stop LOW FOG Generator
Using non refrigerated compressed liquid CO₂ as a coolant



- Produces the **DENSIEST** Low Fog •
- Longest hanging time •
- Lowest fluid consumption •
- Noiseless •
- Adjustment of output •
- Three safety systems •

TECHNICAL DATA

CO₂ type:	Non refrigerated compressed liquid CO ₂
CO₂ consumption:	1,35 kg (3 lb) per minute at full volume
Fluid type:	MDG Low Fog Fluid only – M.S.D.S. available on request
Fluid consumption:	0,04 l (1,23 oz) per minute at full volume
Fluid bottle:	2,5 l (0,66 US gallon)
Fog color:	Pure white
Particle size:	1 - 3 microns
Warm-up time:	10 min.
Operating voltage:	115 or 230 VAC, 50/60Hz
Power consumption:	1450 Watts
Noise emission:	59,2 dB(A) at 1 metre (3,3 ft)
Dimensions:	1,37 m (54")L * 56 cm (22")W * 51 cm (20")H
Weight:	61 kg (135 lb)
Approval:	CE approved, CSA and UL pending



Les Générateurs de Brouillard MDG Ltée / MDG Fog Generators Ltd
5639 Christophe-Colomb, Montreal, QC, Canada H2S 2E8
Tel: 514 272-6040 / 800 663-3020 • Fax: 514 722 3229
www.MDGFOG.com • e-mail: info@MDGFOG.com

